

ACO Self

Residential & Landscape Products

HexaLine - Brickslot is a recyclable polypropylene slotted trench drain system that provides effective, yet discreet drainage in domestic paver or tile installation.


Access to the system for maintenance is through the removable cover on the corner unit.

Suitable for pedestrian/light vehicle traffic applications:

- Residential driveways
- Patios
- Walkways
- Doorways
- Pools




Product Overview



Part Table

	Part No.	Length inches	Width inches	Height inches	Wgt. lbs.
Black channel with plastic slot cover (1 meter)	319555	39.4	4.8	5.4	3.9
Brickslot corner unit	319560	4.8	4.8	7.2	3.0
Accessory pack - 2 end caps, bottom outlet & leaf guard	19303	39.4	5.1	3.2	0.4

Installation Diagram



Accessories

Corner unit:

Allows up to 4 channel connection. Use as access to outlet pipes for maintenance

* Requires 4" flex adaptor to fit to outlet pipe or use vertical bottom outlet adapter on channel



Accessory pack including:

2 - closing end caps



1 - vertical outlet



1 - leaf guard



Installation Instructions



Excavate area to accommodate trench drain and 4" concrete surround, compact base.



Lay 4" deep concrete bed. Cut channels to fit required length (if necessary).



Knockout channel base for outlet at required position.



Push-fit outlet adaptor into bottom of channel. Lay outlet channel first and connect to 3" or 4" SDR pipe or 4" schedule 40. Or use 4" flex coupling to connect 4" SDR pipe to outlet on base of corner unit. Set in place and lay channels from that point.



HexaLine - Brickslot is easily cut using a hacksaw. Channels have a half meter (19.69") cutting guide.



Lay remaining channels; units slide-fit together. Finish pavement/pavers must be an 1/8" higher than edges of drain. Bond pavers to cover and concrete haunch to prevent damage to slot when trafficked.

For pedestrian only applications, trench drain can be set directly on well compacted soil.
For driveway applications, trench drain MUST be surrounded by 4" of concrete.

ACO Polymer Products, Inc.

East Sales Office
9470 Pinecone Drive
Mentor, OH 44060
Tel: (440) 639-7230
Toll free: (877) 553-9961
Fax: (440) 639-7235

Southeast Sales Office
4211 Pleasant Road
Ft. Mill, SC 29708
Toll free: (877) 553-9961
Fax: (803) 802-1063

West Sales Office
825 W. Beechcraft St.
Casa Grande, AZ 85122
Tel: (520) 421-9988
Toll Free: (877) 553-9961
Fax: (520) 421-9899

Electronic Contact
info@acoself.com
www.acoself.com

Follow us on

